

**Compact and Filterless 21klm 4K+ 3-Chip DLP™ Projector
Leverages SOLID SHINE Laser Technology
for Awesome Large-Format Pictures and Low TCO**



20,000lm 4K+ 20,000:1

Item	Description	
DLP™chip	22.9 mm (0.9 in) diagonal (16:10 aspect ratio) DLP™chip ×3	
해상도	4K+ (5120 x 3200 pixels) (Quad Pixel Drive: ON)	
광 원	Laser diodes (광원수명 - Normal : 20,000h / Eco : 24,000h)	
밝 기	20,000lm / 21,000lm (Center)	
명암비	20,000:1 (Full On/Full Off , Dynamic Contrast Mode: 3)	
주변조도비	90%	
스크린 사이즈	1.78–25.4 m (70–1,000 in) with 16:10 aspect ratio 1.78–15.24 m (70–600 in) with the ET-D75LE8 / ET-D3LET80, 16:10 aspect ratio 3.05–15.24 m (120–600 in) with the ET-D75LE95, 16:10 aspect ratio	
렌즈	Optional (no lens included with this model)	
터미널	SDI IN 1	BNC x 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-A), Dual-link 3G-SDI (Link 1), Quad-link HD/3G-SDI (Link 1)
	SDI IN 2	BNC x 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-B), Dual-link 3G-SDI (Link 2), Quad-link HD/3G-SDI (Link 2)
	SDI IN 3	BNC x 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-A), Dual-link 3G-SDI (Link 1), Quad-link HD/3G-SDI (Link 3)
	SDI IN 4	BNC x 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-B), Dual-link 3G-SDI (Link 2), Quad-link HD/3G-SDI (Link 4)
	MULTI PROJECTOR SYNC IN	BNC x 1
	MULTI PROJECTOR SYNC OUT	BNC x 1
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control
	REMOTE 1 IN	M3 x 1 for wired remote control, link control
	REMOTE 1 OUT	M3 x 1 for wired remote control, link control
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
	DIGITAL LINK/LAN	RJ-45 x 1 for network, DIGITAL LINK connection(HDBaseT™ compliant), 100Base-TX, compatible with Art-Net,PJLink™ (class 2), Deep Color, HDCP 2.2
	DC 1/2 OUT	USB Type A x 2 (for power supply DC 5 V total of 2 A)
	Expansion Slot	SLOT 1 / SLOT 2 (total two terminals, vacant) for interface boards, SLOT NX compatible
키스톤 보정	수직: ±40° (±28° with the ET-D75LE6 , ±22° with the ET-D75LE50 , 0~+5° with the ET-D75LE90) 수평: ±15° (cannot be operated when used with the ET-D75LE90)	
렌즈쉬프트	수직: ±59 % (±56 % with ET-D75LE6 / ET-D3LEW60, +69~+84 % with ET-D75LE95) (powered) 수평: ±29 % (±19 % with ET-D75LE6 / ET-D3LEW60, ±21 % with ET-D75LE95) (powered)	
전원	AC 200–240 V, 50/60 Hz; AC 100–200 V, 50/60 Hz (brightness is restricted with lower voltage)	
소음	46dB	
소비전력	1650W (Nomal : 1,140W/ Eco : 1,380W / Standby : 4W)	
크기(W×H×D)	598 × 270 × 725 mm (not including protruding parts)	
무게	54 kg (122 lbs.)	