

Ultra-Bright 4K+ SOLID SHINE Laser Projector Delivers Flagship Image Quality for Rental and Staging



30,500lm | WUXGA | 20,000:1

Item	Description	
DLP™ chip	24.4mm (0.96") (16:10 비율) DLP™ chip ×3	
해상도	WUXGA (1920 x 1200 pixels)	
광 원	Laser diodes (광원수명 - Nomal : 20,000h / Eco : 24,000 h / Quiet : 26,000 h)	
밝 기	30,500 lm/ 32,000lm(Center) (Eco : 24,000 lm / Quiet : 20,000 lm)	
명암비	20,000:1 (Full On/Full Off , Dynamic Contrast Mode: 3)	
주변조도비	90%	
스크린 사이즈	1.78-25.4 m (70-1,000 in) with 16:10 aspect ratio	
	1.78-15.24 m (70-600 in) with the ET-D75LE8, ET-D3LET80 16:10 aspect ratio	
	5.08-15.24 m (200-600 in) with the ET-D3LEW200, ET-D3LEU100 16:10 aspect ratio	
	3.05-15.24 m (120-600 in) with the ET-D75LE95, 16:10 aspect ratio	
렌즈	Optional (no lens included with this model)	
터미널	SDI IN	BNC x 1: 3G/HD-SDI input
	HDMI IN	HDMI x 1, HDCP 2.2 compatible, Deep Color compatible
	DVI-D IN	DVI-D 24 p x 1, single link, DVI 1.0 compliant, HDCP compatible
	MULTI PROJECTOR SYNC IN terminal/3D SYNC 1 IN/OUT terminal (dual)	BNC x 1, TTL high impedance
	MULTI PROJECTOR SYNC OUT terminal/3D SYNC 2 OUT terminal (dual)	BNC x 1, TTL output: Maximum 10 mA
	SERIAL IN	D-Sub 9 p x 1, RS-232C compliant, for computer control
	SERIAL OUT	D-Sub 9 p x 1, RS-232C compliant, for computer control
	REMOTE 1 IN	M3 stereo mini jack x 1, for remote control (wired)/for projector connection control
	REMOTE 1 OUT	M3 stereo mini jack x 1, for remote control (wired)/for projector connection control
	REMOTE 2 IN	D-Sub 9 p x 1, for contact control
	DIGITAL LINK/LAN	USB connector (type A) x 1, for connecting the optional Wireless Module (Model No.: AJ-WM50 Series)
	DC OUT 1 / DC OUT 2	USB connector (type A) x 2, for power supply only (DC 5 V, 2 A total for two terminals)
SLOT	SLOT x 1, SLOT NX specification, for installing the Interface Board	
키스톤 보정	수직: ±45 ° (± 40 ° with ET-D75LE10/ET-D3LEW10/ET-D75LE20/ET-D3LES20, ±28 ° with ET-D75LE6/ET-D3LEW60, ±22 ° with ET-D3LEW50, ±15 ° with ET-D3LEW200, ±8 ° with ET-D3LEU100, +5 ° with ET-D75LE95) 수평: ±40 ° (±15 ° with ET-D3LEW50/ET-D75LE6/ET-D3LEW60, ±5 ° with ET-D3LEU100/ET-D3LEW200, 0 ° with ET-D75LE95)	
렌즈유프트	수직: ±55 % (±44 % with ET-D75LE6, +68 % - +78 % with ET-D75LE95, ±55% with ET-D3LEU100, ±48% with ET-D3LEW200) (powered) 수평: ±20 % (±15 % with ET-D75LE6, ±12 % with ET-D75LE95, 0-+25% with ET-D3LEU100, ±15% ET-D3LEW200) (powered)	
전원	AC100 V-AC120 V/AC200 V-AC240 V 50 Hz/60 Hz AC100 V-AC120 V, 50 Hz/60 Hz (Brightness is restricted to approximately 1/3)	
소음	Nomal : 49 dB / Quiet : 46 dB	
소비전력	2,450 W (Nomal : 2,010W / Eco : 1,590W / Quiet : 1,310W / Standby : 13W)	
크기(W×H×D)	598 x 353 x 780 mm (including protruding parts)	
무게	68.6 kg (152 lbs)	