

*More Immersive Color-rich Images
form Our Most Adaptable Projector Yet*



8,000lm 4K 10,000:1

Item	Description	
DLP™ chip	17.0 mm (0.67") 대각 (16:10 화면 비율) , DLP™ chip × 1	
해상도	4,608,000 pixels (2715x1697) pixels (when Smooth Pixel Drive ON)	
광원	Laser diodes (광원수명 - Nomal : 20,000 h / Eco : 24,000 h)	
밝기	8,000 lm / 8,400 lm (Center)	
명암비	10,000:1 (Full On/Full Off, Dynamic Contrast Mode: ON)	
주변조도비	90%	
스크린 사이즈	1.27- 15.24 m (50- 600 inches) (16:10 aspect ratio) 2.54- 10.15m (100- 400 inches) with the ET-DLE020 (16:10aspect ratio) 1.27- 5.08 m (50-200 inches) with the ET-DLE055 (16:10 aspect ratio) 2.54- 8.89 m (100-350 inches) with the ET-DLE035 (16:10 aspect ratio)	
렌즈	Powered zoom/focus lenses (1.7-2.4:1), F 1.7-1.9, f 25.6-35.7 mm	
단자	SDI IN	BNC × 1: 3G/HD-SDI input
	HDMI IN	HDMI 19-pin × 1 (Deep Color, compatible with HDCP 2.2, 4K/60p signal input)
	DVI-D IN	DVI-D 24-pin × 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
	MULTI PROJECTOR SYNC IN	BNC x 1
	MULTI PROJECTOR SYNC OUT	BNC x 1
	SERIAL IN	D-sub 9-pin (female) × 1 for external control (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) × 1 for link control
	REMOTE 1 IN	M3 x 1 for wired remote control
	REMOTE 1 OUT	M3 x 1 for link control (for wired remote control)
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
	LAN	RJ-45 × 1 for network connection,10Base-T/100Base-TX, compliant with PLink™ (Class 2), Art-Net
	DIGITAL LINK	RJ-45 x 1 for network, DIGITAL LINK connection (HDBaseT™ compliant), 100Base-TX, compatible with Art-Net, PLink™ (Class 2), Deep Color, HDCP 2.2, 4K/60p signal input
	USB	USB Connector (Type A) x 1 for Cloning/Wireless Module (output 5 V/500 mA)
Expansion Slot	Open slot for SLOT NX compatible interface board	
렌즈슈프트	수직: -16~+50 % (-16~+40 % with ET-DLE060) (powered) 수평: -10~+30 % (-20~+10 % with ET-DLE020, -10~+19 % with ET-DLE060, -10~+28 % with ET-DLE105/ET-DLE085) (powered)	
키스톤 보정	수직: ±40 ° (±5 ° with ET-DLE020, ±16 ° with ET-DLE060, ±22 ° with ET-DLE105/DLE085/DLE055, +5 ° with ET-DLE035), 수평: ±15 ° (±10 ° with ET-DLE060) (cannot be operated with ET-DLE035/ET-DLE020)	
전원	AC 100-240 V, 50/60 Hz	
소비전력	880 W (Nomal : 770 W / Eco : 590 W / Shutter : 100 W / Standby : 8 W)	
크기(W×H×D)	498 x 200 x 581 mm (with lens) / 498 x 200 x 538 mm (without lens)	
무게	Approx. 24.2 kg (with lens) / 23.4 kg (without lens)	
캐비닛 재질	몰드 플라스틱	
소음	Nomal : 40 dB / Quiet : 38 dB	
작동 환경	작동 온도 : 0°C- 45°C, 작동 습도 : 10 - 80 % (무결로)	