

**Packing 12,000lm Brightness
into a Compact Body, the PT-RZ120 Dual-Drive
SOLID SHINE Laser Projector Lets You Do More**



12,000lm	WUXGA	10,000:1
-----------------	--------------	-----------------

Item	Description	
DLP™ chip	17.0 mm (0.67") 대각 (16:10 화면 비율) DLP™ chip x 1	
해상도	WUXGA (1920 x 1200 pixels)	
광원	Laser diodes (광원수명 - Nomal : 20,000 h / Eco : 24,000 h)	
밝기	12,600 Center Lumens / 12,000 ANSI Lumens	
명암비	10,000:1 (Full On/Full Off, Dynamic Contrast Mode: 3)	
주변조도비	90% (Center-to-corner)	
스크린 사이즈	1.27~15.24 m (50~600 in) with ET-DLE055, 1.27~5.08 m (50~200 in) with ET-DLE055, 2.54~8.89 m (100~350 in) with ET-DLE035, 16:10 aspect ratio	
렌즈	Powered zoom (throw ratio 1.7~2.4:1), powered focus F 1.7~1.9, f 25.6~35.7 mm	
단자	SDI IN	BNC x 1: 3G/HD/SD-SDI input
	HDMI IN	HDMI 19-pin x 1 (Deep Color, compatible with HDCP 2.2, 4K signal input)
	DVI-D IN	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
	RGB 1 IN	RGB x 1 (BNC x 5): RGB/YPBPR/YCBCR
	RGB 2 IN	D-sub HD 15-pin (female) x 1: RGB/YPBPR/YCBCR
	SERIAL/MULTI-PROJECTOR	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
	SERIAL/MULTI-PROJECTOR	D-sub 9-pin (male) x 1 for link control
	REMOTE 1 IN	M3 x 1 for wired remote control
	REMOTE 1 OUT	M3 x 1 for link control (for wired remote control)
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
	LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (compatible with PJLink™[Class2], Art-Net)
	DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITAL LINK connection (HDBaseT™ compliant), 100Base-TX (Compatible with PJLink™ [Class 2], Art-Net, HDCP 2.2, Deep Color, 4K signal input)
렌즈슈프트	수직: -16~+50 % (-16~+40% with ET-DLE060) (powered) 수평: -10~+30 % (-10~+19% with ET-DLE060 / -10~+28 % with ET-DLE085/ET-DLE105) (powered)	
키스톤 보정	수직: ±40° (±16° with ET-DLE060, ±40° with ET-DLE150/ET-DLE250/supplied lens, ±22° with ET-DLE105/ET-DLE085/ET-DLE055) 수평: ±15° (±10° with ET-DLE060, ±15° with ET-DLE105/ET-DLE085/ET-DLE055)	
소음	Nomal : 44 dB/ Quiet 1: 41 dB / Quiet 2 : 38 dB	
전원	AC 100~240 V, 50/60 Hz	
소비전력	1100 W (Nomal : 730W / Eco : 590W)	
크기(W×H×D)	498 x 200 x 581 mm (with supplied lens) 498 x 200 x 538 mm (without lens)	
무게	23.6 kg (with supplied lens), 22.8 kg (without lens)	
캐비닛 재질	성형 플라스틱	
작동 환경	작동 온도 : 0°C- 45°C, 작동 습도 : 10 - 80 % (무결로)	