




NEW

UT47WL



**세계에서 가장 밝고 설치가 용이한
HLD LED 초단초점 프로젝터**



Item	Description	
Display Panel	3x0.76" LCD(Liquid Crystal Display) , 16:10 (Standard)/4:3 (Compatible)	
Native Resolution	WXGA (1280x800)	
Light source	HLD Laser	
Brightness	4,700 lm	
Contrast Ratio	3,000,000:1 (IRS ON)	
Screen size	0.504m~0.892m (70"~130")	
Projection Lens	1.05xoptics Manual, 80"@0.468m: 0.27~0.29 : 1 ,F1.78-F1.83, f= 4.92~5.18mm	
Terminal(I/O port)	Input	VGA x 2, Audio in (mini jack,3.5mm) x1, YCbCr/Component x 1. (Share with VGA IN 2) Video x 1 Audio in (L/R) --RCA x 2, S-Video x 1Share with VGA IN 2), HDMI 1.4 x2(One is Compatible with MHL), USB- A x 1 1. Support Memeory viewer, USB- B x 1(Display), RJ45 x 1(Display)
	Output	VGA x 1, Audio out (mini-jack,3.5mm) x 1
	Control	RS232 x 1, RJ45 x 1(Control), USB-B x 1(for up-grade)
Display Resolution	Computer Signal Input	VGA, SVGA, XGA, SXGA,WXGA,UXGA,WUXGA,Mac,
	Video Signal Input	PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, PAL-60, 480i, 480p, 576i, 576p, 720p, 1080p and 1080i
Keystone Correction	V: ±5° (manual) H : ±5° (manual) Pincushion/Barrel Correction Corner Keystone	
Lens Shift	Lens Shift V : ±3%(Manual) Lens Shift H : ±2%(Manual)	
Noise	Normal:37.5dB@1m ECO:33.5dB@1m	
Speaker	10W x 2	
Power Source	100~240V@ 50/60Hz	
Power Consumption	450W (<0.5W)	
Temp. & Humidity	Operating Temp.	0℃~40℃(35~ ECO)
	Operating Humidity	20%~85%
Dimension (W×H×D)	449 x 153 x 425 mm	
Weight	11kg	