

**21,000lm (Center) of Compact SOLID SHINE Laser**  
**Power Goes Filterless for Ultimate Endurance**



**20,000lm | WUXGA | 20,000:1**

Item	Description	
DLP™chip	24.4 mm (0.96" (16:10 비율) DLP™chip ×3	
해상도	6,912,000 (1,920 × 1,200 × 3) pixels	
광 원	Laser diodes (광원수명 - Normal: 20,000H / Eco: 24,000H)	
밝 기	20,000 Lumens / 21,000 Lumens (Center)	
명암비	20,000:1 (Full On/Off)	
주변조도비	90%	
스크린 사이즈	1.78–25.4 m (70–1000 in) with 16:10 aspect ratio 1.78–15.24 m (70–600 in) with the ET-D75LE8, 16:10 aspect ratio 3.05–15.24 m (120–600 in) with the ET-D75LE95, 16:10 aspect ratio	
렌즈	Optional powered zoom/focus lenses and fixed-focus lens	
터미널	SDI IN 1	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-A), Dual-link 3G-SDI (Link 1)
	SDI IN 2	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-B), Dual-link 3G-SDI (Link 2)
	HDMI IN	HDMI × 1 (Deep Color, compatible with HDCP)
	DVI-D IN	DVI-D 24-pin × 1 (DVI 1.0 compliant, compatible with HDCP)(Single-link only)
	RGB 1 IN	RGB × 1 (BNC × 5): RGB/YPBPR/YC/VIDEO
	RGB 2 IN	D-sub HD 15-pin (female) × 1: RGB/YPBPR
	MULTI PROJECTOR SYNC IN/	BNC × 1
	MULTI PROJECTOR SYNC OUT/	BNC × 1
	SERIAL IN	D-sub 9-pin (female) × 1 for external control (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) × 1 for link control
	REMOTE 1 IN	M3 × 1 for wired remote control, link control
	REMOTE 1 OUT	M3 × 1 for wired remote control, link control
	REMOTE 2 IN	D-sub 9-pin (female) × 1 for external control (parallel)
	DC OUT	USB (Type A) × 2, DC 5 V, total of 2 A
DIGITAL LINK/LAN	RJ-45 × 1 for network, DIGITAL LINK connection, 100Base-TX, compatible with Art-Net, PLink™ (Class 2), Deep Color, HDCP	
키스톤 보정	수직: ±40° (±28° with the ET-D75LE6, ±22° with the ET-D75LE50, 0~+5° with the ET-D75LE90) 수평: ±15° (cannot be operated when used with the ET-D75LE90)	
렌즈쉬프트	수직: ±55 % (±44 % with the ET-D75LE6, +68 % - +78 % with the ET-D75LE95) (powered) 수평: ±20 % (±15 % with the ET-D75LE6, ±12 % with the ET-D75LE95) (powered)	
소음	46dB	
전원	AC 200–240 V, 50/60 Hz	
소비전력	1,510 W (Nomal : 1,217 W / Eco : 972 W / Standby : 8 W )	
크기(W×H×D)	598 × 270 × 725 mm (not including protruding parts)	
무게	49kg	