

The World's Smallest and Lightest

5,000lm LCD Laser Projector



**5,000 lm WUXGA 3,000,000 : 1**

Item	Description	
패널	16.3 mm(0.64") (16:10 화면비율) LCD × 3	
해상도	2,304,000 (1,920 x 1,200) x 3, total of 6,912,000 pixels	
광 원	Laser diodes (광원 수명 : 20,000H)	
밝 기	5,000 ANSI Lumens	
명암비	3,000,000:1 (Dynamic Mode/ Dynamic Contrast 1)	
주변조도비	85%	
스크린 크기	0.76-7.62 m (30-300 in) 16:10 aspect ratio	
렌즈	1.6x Manual zoom (Throw Ratio 1.09 – 1.77 :1), Manual focus ( F = 1.60 – 2.12, f = 15.30 – 24.64 mm)	
터미널	COMPUTER 1 IN	high-density D-Sub 15 p (female) x1
	COMPUTER 2 IN / 1 OUT	high-density D-Sub 15 p (female) x1
	VIDEO IN	Pin jack x1 1.0 Vp-p, 75 ohms
	HDMI 1 IN / HDMI 2 IN	HDMI 19 pin x2, HDCP and Deep color compatible / Audio signals : Linear PCM
	AUDIO 1/2 IN	M3 stereo mini jack x2, 0.5 V[rms], input Impedance 22 k ohms and more
	AUDIO 3 IN	Pin jack x 2(L-R), 0.5 V[rms], input Impedance 22 k ohms and more
	VARIABLE AUDIO OUT	M3 stereo mini jack +1, 0 V[rms] to 2.0 V[rms] variable, output Impedance 2.2 k ohms
	USB	USB connector(type A)+1 for memory viewer/wireless module (Output 5V MAX 2A On standby)
	SERIAL IN	D-sub 9 pin +1, RS-232C compliant, for computer control use
	DIGITAL LINK/LAN	RJ-45 × 1 for network and DIGITAL LINK (video/network/serial control) (HDBase™ compliant), PLink™ (class 2)compatible, 100Base-TX, HDCP compatible, Deep Color compatible 4K/30p signal input compatible
LAN	RJ-45 × 1 for network connection, PLink™ (class 2) compatible, 10Base-T/100Base-TX	
키스톤 보정	수직: ±25° , 수평: ±35°	
렌즈쉬프트	수직: 0~44 % (Manual) 수평: ±20% (Manual)	
소음	Nomal : 37 dB / Eco : 27 dB	
스피커	10W	
전원	100-240 V AC, 50/60 Hz	
소비전력	370W (Nomal : 330W / Eco : 235W / Quiet : 230W / 대기 : 18W )	
크기(W×H×D)	399 x 115 x 348 mm (Not including protruding parts)	
무게	약 7.2kg (표준렌즈 포함)	