

**Bright SOLID SHINE Laser LCD Projectors**  
**Blend High Performance and Low Running Costs for**  
**Best Value in Mid-sized Venues**



**8,000lm** | **WXGA** | **3,000,000:1**

Item	Description	
패널	19.3mm (0.76") (16:10 비율) LCD × 3	
해상도	WXGA (1,280 x 800 pixels), total of 3,072,000 pixels	
광 원	Laser diodes (광월수명 : 20,000H)	
밝 기	8,000 Lumens	
명암비	3,000,000:1 (Dynamic Mode/Dynamic Contrast 1/2)	
주변조도비	90%	
스크린 사이 즈	1.02~10.16 m (40~400 in), 16:10 aspect ratio 1.52~10.16 m (60~400 in) with the ET-ELW22, 16:10 aspect ratio	
렌즈	1.6x Powered zoom (throw ratio 1.6~2.8 :1), F = 1.7~2.3, f = 26.8~45.5 mm	
터미널	HDMI 1/2 IN	HDMI 19-pin × 2 (Deep Color, compatible with HDCP)
	RGB 1 IN	RGB × 1 (BNC × 5): RGB/YPBPR/YCBCR
	RGB 2 IN	D-sub HD 15-pin (female) × 1: RGB/YPBPR/YCBCR
	VIDEO IN	Pin jack × 1
	MONITOR OUT	D-sub HD 15-pin (female) × 1: RGB/YPBPR/YCBCR
	AUDIO 1/2 IN	M3 stereo mini jack (L-R) × 2
	AUDIO 3 IN	Pin jack × 2 (L-R) × 1
	AUDIO OUT	M3 stereo mini-jack × 1 for output
	SERIAL IN	D-sub 9-pin (female) × 1 for external control (RS-232C compliant)
	REMOTE 1 IN	D-sub 9-pin (female) × 1 for external control (parallel)
	REMOTE 2 IN	M3 × 1 for wired remote control
	LAN	RJ-45 × 1 for network connection, 10Base-T, 100Base-TX, compatible with PLink™ (Class 2)
	LAN/DIGITAL LINK	RJ-45 × 1 for network and DIGITAL LINK connection HDBase-T™ compliant (Compatible with PLink™, HDCP, Deep Color)
	Memory Viewer/Pairing	USB (Type A) × 1
DC OUT	USB (Type A) × 1 for power supply (DC 5 V/max. of 2 A)	
키스톤 보정	수직: ±35° 수평: ±35°	
렌즈쉬프트	수직: ±67 % (powered) 수평: ±35 % (powered)	
소음	Nomal/Eco : 35 dB / Quiet : 28 dB	
스피커	4.0cm 둥근형태 / 10W	
전원	100-240 V AC, 50/60 Hz	
소비전력	545W ( Standby[Nomal] : 22W / Standby[Eco] : 0.5W)	
크기(W×H×D)	560 x 205 x 443 mm (with supplied lens) / 560 x 205 x 428 mm (without lens)	
무게	Approximately 17.1kg (with supplied lens) / 16.2 kg (without lens)	