

*The New Era of Professional Visual Imaging
Higher Brightness, Picture Quality and
Reliability – All in a Compact Body*



12,000lm | WUXGA | 10,000:1

Item	Description	
DLP™chip	24.4 mm (0.96") (16:10 비율) DLP™chip ×3	
해상도	WUXGA (1,920 x 1,200 pixels)	
램 프	380W UHM lamps (High Mode) x 2	
밝 기	12,000 ANSI Lumens (Dual-lamp, high mode)	
명암비	10,000:1 (Full On/Off)	
주변조도비	90%	
스크린 사이 즈	1.78 – 25.4m (70–1,000 inches), 1.78 – 15.24m (70–600 inches with the ET-D75LE8) (16:10 화면비율)	
렌즈	Optional powered zoom/focus lenses and fixed-focus lens	
터미널	SDI 1 IN	BNC x 1 (3G/HD/SD-SDI)
	SDI 2 IN	BNC x 1 (HD/SD-SDI)
	HDMI IN	HDMI 19-pin x 1 (Deep Color, compatible with HDCP)
	DVI-D IN	DVI-D 24-pin × 1, DVI 1.0 compliant, HDCP compatible, for single link only
	RGB1 IN	BNC x 5 (RGB/YBPBR/YCBCR/YC x 1)
	RGB2 IN	D-Sub HD 15-pin (female) x 1 (RGB/YBPBR/YCBCR x 1)
	VIDEO IN	BNC x 1 (composite video)
	3D SYNC 1 IN/OUT	BNC × 1
	3D SYNC 2 OUT	BNC × 1
	SERIAL IN	D-sub 9-pin (female) x 1(RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) x 1(RS-232C compliant)
	REMOTE 1 IN	M3 x 1 for wired remote control
	REMOTE 1 OUT	M3 x 1 for link control (for wired remote control)
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
LAN	RJ-45 x 1 (network connection, 10Base-T/100Base-TX, compliant with PLink™)	
키스톤 보정	수직 : ±40 ° (±28 ° with the ET-D75LE6 , ±22 ° with the ET-D75LE5/D75LE50) 수평 : ±15 °	
렌즈쉬프트	수직 : ±55 % (±44 % with the ET-D75LE6) 수평 : ±20 % (±15 % with the ET-D75LE6)	
소음	High : 45 dB / Middle : 43 dB / Eco : 37 dB	
전원	200–240 V AC, 50/60 Hz	
소비전력	120V AC: 1,000W(1,030VA), 220-240V AC: 970W(1,020VA)	
크기(W×H× D)	530×200×548.5mm (without lens)	
무게	24kg (without lens)	