

## Introducing the World's Lightest 3-Chip DLP™ Laser Projector with 4K+ Resolution



\* Resolution 5120 x 3200 Pixels (QUAD PIXEL DRIVE: ON)



<b>10,000lm</b>	<b>4K+</b>	<b>20,000:1</b>
-----------------	------------	-----------------

Item	Description	
DLP™chip	22.9 mm (0.9") (16:10 비율) DLP™chip ×3	
해상도	12,288,000 (2560 x 1600 x 3) pixels when Quad Pixel Drive set to OFF	
광 원	Laser diodes (Normal: 20,000H / Eco: 24,000H)	
밝 기	10,000 Lumens	
명암비	20,000:1 (Full On/Off)	
주변조도비	90%	
스크린 사이즈	1.78 – 25.4m (70–1,000 inches) with 16:10 aspect ratio 1.78 – 15.24m (70-600 inches) with the ET-D75LE8 , 16:10 aspect ratio 3.05 – 15.24m (120–600 inches) with the ET-D75LE90 , 16:10 aspect ratio	
렌즈	Optional powered zoom/focus lenses and fixed-focus lens	
터미널	SDI IN 1	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI(LINK-A), Dual-link 3D-SDI(LINK 1), Quad-link 3G/HD-SDI(LINK 1)
	SDI IN 2	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI(LINK-B), Dual-link 3D-SDI(LINK 2), Quad-link 3G/HD-SDI(LINK 2)
	SDI IN 3	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI(LINK-A), Dual-link 3D-SDI(LINK 1), Quad-link 3G/HD-SDI(LINK 3)
	SDI IN 4	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI(LINK-B), Dual-link 3D-SDI(LINK 2), Quad-link 3G/HD-SDI(LINK 4)
	Frame Sync 1 IN/OUT	BNC × 1: Frame-synchronizing timing signal
	Frame Sync 2 OUT	BNC × 1: Frame-synchronizing timing signal
	SERIAL IN	D-sub 9-pin (female) × 1 for external control (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) × 1 for link control
	REMOTE 1 IN	M3 × 1 for wired remote control
	REMOTE 1 OUT	M3 × 1 for link control (for wired remote control)
	REMOTE 2 IN	D-sub 9-pin (female) × 1 for external control (parallel)
	DIGITAL LINK/LAN	RJ-45 × 1 for network, DIGITAL LINK connection (HDBase™ compliant ), 100Base-TX, compatible with Art-Net, PLink™ (class 1), Deep Color, HDCP 2.2
	Expansion Slot	× 2 (SLOT 1, SLOT 2) (Compatible with optional Input Board/Terminal Board)
키스톤 보정	수직: ±40° (±28° with the ET-D75LE6 , ±22° with the ET-D75LE50 , 0~+5° with the ET-D75LE90) 수평: ±15° (cannot be operated when used with the ET-D75LE90)	
렌즈슈프트	수직: ±59 % (±44 % with the ET-D75LE6 , +74 %~+84 % with the ET-D75LE90) (powered) 수평: ±29 % (±19 % with the ET-D75LE6 , -12 % – +16 % with the ET-D75LE90) (powered)	
소음	46dB	
전원	AC 100–120 V, 200–240 V, 50/60 Hz	
소비전력	1270 W (Nomal : 913 W / Eco : 782 W / Long Life 1 : 531-732 W / Long Life 2 : 477-702 W / Long Life 3 : 423-665 W)	
크기(무장착)	578 × 270 × 725 mm (렌즈 미포함), 578 x 323.5 x 740 mm (렌즈포함)	
무게	49 kg (렌즈 무장착)	