

Ultra-High Brightness 3-Chip DLP™ SOLID SHINE
Laser Projectors for Large Venues



30,000lm | **WUXGA** | **20,000:1**

Item	Description	
DLP™ chip	24.4mm (0.96") (16:10 비율) DLP™ chip × 3	
해상도	WUXGA (1,920 × 1,200 pixels)	
광 원	Laser diodes (광원수명 - Normal: 20,000H / Long life3: 87,600H)	
밝 기	High : 30,000lm/31,000lm(Center) / Nomal : 25,000lm/26,000 lm(Center)	
명암비	20,000:1 (Full on/off, with Dynamic Contrast Mode set to "3")	
주변조도비	90%	
스크린 사이즈	1.78–25.4 m (70–1000 in) with 16:10 aspect ratio 1.78–15.24 m (70–600 in) with the ET-D75LE8, 16:10 aspect ratio 3.05–15.24 m (120–600 in) with the ET-D75LE95, 16:10 aspect ratio	
렌즈	Optional powered zoom/focus lenses and fixed-focus lens	
터미널	SDI IN 1	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (LINK-A), Dual-link 3G-SDI (LINK 1)
	SDI IN 2	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (LINK-B), Dual-link 3G-SDI (LINK 2)
	HDMI IN	HDMI 19-pin × 1 (Deep Color, compatible with HDCP)
	DVI-D IN	DVI-D 24-pin × 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
	RGB 1 IN	RGB × 1 (BNC × 5): RGB/YBPBR/YCBCR/YC/VIDEO
	RGB 2 IN	D-sub HD 15-pin (female) × 1: RGB/YBPBR/YCBCR
	MULTI PROJECTOR SYNC IN/	BNC × 1
	MULTI PROJECTOR SYNC OUT/ 3D SYNC 2 OUT	BNC × 1
	SERIAL IN	D-sub 9-pin (female) × 1 for external control (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) × 1 for link control
	REMOTE 1 IN	M3 × 1 for wired remote control
	REMOTE 1 OUT	M3 × 1 for link control
	REMOTE 2 IN	D-sub 9-pin (female) × 1 for external control (parallel)
	DIGITAL LINK/LAN	RJ-45 × 1 for network, DIGITAL LINK connection, 100Base-TX, compatible with Art-Net, PJLink™ (class 1), Deep Color, HDCP
DC OUT	USB Type A × 2 for power supply (DC 5 V, max 900mA)	
키스톤 보정	수직: ±40° (±28° with the ET-D75LE6 , ±22° with the ET-D75LE50 , 0~+5° with the ET-D75LE90) 수평: ±15° (cannot be operated when used with the ET-D75LE90)	
렌즈쉬프트	수직: ±55 % (±44 % with the ET-D75LE6, +68 % - +78 % with the ET-D75LE95) (powered) 수평: ±20 % (±15 % with the ET-D75LE6, ±12 % with the ET-D75LE95) (powered)	
소음	49dB	
전원	AC 200-240 V, 50/60 Hz [AC 100-120 V, 50/60 Hz (brightness is restricted with lower voltage)]	
소비전력	2,870 W (Nomal : 1,890 W / High : 2,310 W / Long Life 1 : 1,040-1,680 W / Long Life 3 ; 794-1,460 W)	
크기(W×H×D)	700 × 418 × 1,250mm(including protruding parts) / 700 × 373 × 1,070mm (without protrusion parts)	
무게	79kg	