

Well-Balanced Color and Brightness,
Seamlessly Integrated into
Environment and Infrastructure



8,000lm | **WUXGA** | **3,000,000:1**

Item	Description	
패널	19.3 mm (0.76") (16:10 비율) LCD × 3	
해상도	WUXGA (1,920 x 1,200 pixels)	
광 원	Laser diodes (광원수명 : 20,000H)	
밝 기	8,000 Lumens	
명암비	3,000,000:1 (Dynamic Mode/Dynamic Contrast 1/2)	
주변조도비	85%	
스크린 사이즈	1.02-10.16 m (40-400 in), 16:10 aspect ratio 1.52-10.16 m (60-400 in) with the ET-ELW22, 16:10 aspect ratio 2.54-10.16 m (100-400 in) with the ET-ELU20, 16:10 aspect ratio	
렌즈	전동 줌 (throw ratio 1.61-2.76 :1), 전동 포커스 F = 1.7-2.3, f = 26.8-45.5 mm (for supplied lens)	
터미널	HDMI 1/2 IN	HDMI 19-pin ×3(Compatible with HDCP 2.3,Deep Color,4K/60p*5 signal input),CEC supported
	COMPUTER IN□	D-sub HD 15-pin (female) x 1 (RGB/YPBPR/YCBCR)
	MONITOR OUT□	D-sub HD 15-pin (female) x 1 (RGB/YPBPR/YCBCR)
	SERIAL/MULTI SYNC IN□	D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)
	MONITOR OUT	D-sub HD 15-pin (female) x 1: RGB/YPBPR/YCBCR
	MULTI SYNC OUT□	D-sub 9-pin (male) x 1 for link control
	REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
	AUDIO IN	M3 stereo mini-jack x 1
	AUDIO OUT	M3 stereo mini-jack x 1
	DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p*5*6 signal input)
	LAN	RJ-45x1 for network connection,10Base-T,100Base-TX(Compatible with PLink™[Class 2])
DC OUT□	USB Connector (Type A) x 1 (Output 5 V/2 A)	
키스톤 보정	수직: ±25°, 수평: ±30°	
렌즈쉬프트	수직: ±67 % (powered), 수평: ±35 % (powered)	
소음	Nomal/Eco : 34 dB, Quiet : 27 dB	
전원	100-240 V AC, 50/60 Hz	
소비전력	[MAX] 490 W (5.4-2.6 A) (510VA), 465W (200-240 V) [NORMAL]: 435 W (100-120 V), 415 W (200-240 V) [ECO]: 315 W (100-120 V), 300 W (200-240 V) [QUIET]: 310 W (100-120 V), 295 W (200-240 V)	
크기(W×H×D)	561 x 224 x 439 mm (with supplied lens)	
무게	Approximately 18.6kg (with supplied lens)	