



## SOLID SHINE LCD Boosts Image

Brightness While Reducing Your Workload,  
Delivering an Effortless Learning Experience



**13,000lm** | **3,000,000:1** | **WUXGA**

Item	Description	
패널	25.4 mm (1.0") (16:10 비율) LCD × 3	
해상도	WUXGA (1,920 x 1,200 pixels)	
광 원	Laser diodes (광원수명 : 20,000H)	
밝 기	13,000 Lumens	
명암비	3,000,000:1 (Full On/Full Off)	
주변조도비	85%	
스크린 크기	2.03~12.7 m (80~500 in), 16:10 aspect ratio	
렌즈	Optional powered zoom lenses	
터미널	SDI IN	BNC x 1: 3G/HD/SD-SDI input
	HDMI IN	HDMI 19-pin x 1 (Compatible with HDCP2.2, Deep Color, 4K/60p signal input)
	DVI-D IN	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
	RGB IN	D-sub HD 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
	SERIAL/MULTI PROJECTOR SYNC IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
	SERIAL/MULTI PROJECTOR SYNC	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
	REMOTE 1 IN	D-sub 9-pin (female) × 1 for external control (parallel)
	REMOTE 2 IN	M3 x 1 for wired remote control
	REMOTE 2 OUT	M3 x 1 for link control (for wired remote control)
	DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase1™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.2, Deep Color, 4K/60p signal input)
	LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PLink™ [Class 2], Art-Net)
	USB	USB Connector (Type A) x 1 (Output 5 V/2 A)
키스톤 보정	수직: ±40° (±14° with ET-EMW200/EMW300, ±22° with ET-EMW400/EMW500, ±40° with ET-EMT700/EMT800 ), 수평: ±15° (±8° with ET-EMW200/EMW300, ±15° with ET-EMW400/EMW500/EMT700/EMT800)	
렌즈슈프트	수직: ±60 % (±40 % with ET-EMW200, ±50 % with ET-EMW300) (powered) 수평: ±20 % (±19 % with ET-EMW200, ±20 % with ET-EMW300) (powered)	
소음	Nomal : 35 dB / Quiet : 30 dB	
전원	100-240 V AC, 50/60 Hz	
소비전력	800W (Nomal : 740W / Quiet : 530W / Shutter : 85W)	
크기(W×H×D)	650 x 211 x 440 mm (Without lens)	
무게	Approximately 22.3kg	