

Blending High-Brightness SOLID SHINE Laser
with Quality LCD Imaging in a Flexible Solution



6,500lm	WUXGA	3,000,000:1
----------------	--------------	--------------------

Item	Description	
패널	19.3mm (0.76") (16:10 비율) LCD × 3	
해상도	WUXGA (1,920 × 1,200 pixels), total of 6,912,000 pixels	
광 원	Laser diodes (광원수명 : 20,000H)	
밝 기	6,500 Lumens	
명암비	3,000,000:1 (Full on/off, Dynamic Contrast Mode: ON)	
주변조도비	90%	
스크린 사이 즈	1.02~10.16 m (40~400 in) 16:10 aspect ratio 1.52-10.16 m (60-400 in) with the ET-ELW22, 16:10 aspect ratio	
렌즈	1.6x Powered zoom (Throw Ratio 1.6~2.8 :1), F = 1.7~2.3, f = 26.8~45.5 mm	
터미널	HDMI IN	HDMI 19-pin × 2 (Deep Color, compatible with HDCP)
	RGB 1 IN	BNC × 5 (RGB or YPB PR/YCBCR × 1)
	RGB 2 IN	D-sub HD 15-pin (female) × 1 (compatible with component input)
	VIDEO IN	Pin jack × 1 (composite video)
	MONITOR OUT	D-sub HD 15-pin (female) × 1 (RGB × 1) (compatible with RGB or YPB PR/YCBCR)
	AUDIO IN	Pin jack × 2 (L/R × 1), M3 × 2 (L-R × 2)
	AUDIO OUT	M3 × 1 (L-R × 1) for output (variable)
	SERIAL IN	D-sub 9-pin (female) × 1 for external control (RS-232C compliant)
	REMOTE 1 IN	D-sub 9-pin (female) × 1 for external control (parallel)
	REMOTE 2 IN	M3 × 1 for wired remote control
	LAN	RJ-45 × 1 for network connection, 10Base-T, 100Base-TX, compatible with PLink™(Class 2)
	LAN/DIGITAL LINK	RJ-45 × 1 for network and DIGITAL LINK connection, 100Base-TX, compatible with PLink™(Class 2), HDCP, Deep Color
	Memory Viewer/Pairing	USB (Type A) × 1
	DC OUT	USB (Type A) × 1, DC 5 V/2 A
키스톤 보정	수직: ±25 ° 수평: ±30 °	
렌즈쉬프트	수직: ±67 % (powered) 수평: ±35 % (powered)	
스피커	4.0cm 둥근형태 / 10W	
소음	Nomal/Eco : 32 dB / Quiet : 26 dB	
전원	100-240 V AC, 50/60 Hz	
소비전력	525W (Standby[Nomal] : 22W / Standby[Eco] : 0.5W)	
크기(W×H×D)	560 × 205 × 443 mm (with supplied lens) / 560 × 205 × 428 mm (without lens)	
무게	16.9kg (with supplied lens) / 16.1 kg (without lens)	