

**Compact 17,000 lm Projector Delivers
Stunning Picture Quality with High Frame-Rate**



17,000lm	WXGA	10,000:1
-----------------	-------------	-----------------

Item	Description	
DLP™ chip	21.6 mm (0.85") (16:9 비율) DLP™ chip × 3	
해상도	1,049,088 (1,366 x 768) x 3, total of 3,147,264 pixels	
램프	432 W UHM lamp x 4 (램프수명 :	
밝기	17,000 ANSI Lumens	
명암비	10,000:1 (Full On/Off)	
주변조도비	90%	
스크린 사이즈	1.78 – 25.4m (70–1,000 inches), 1.78 – 15.24m (70–600 inches) with the ET-D75LE8, 16:9 aspect ratio	
렌즈	Optional powered zoom and fixed-focus lens	
터미널	DVI-D IN	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
	HDMI IN	HDMI 19-pin x 1 (Deep Color, compatible with HDCP)
	RGB 1 IN	BNC x 5 (RGB/YBPBR/YCBCR/YC x 1)
	RGB 2 IN	D-sub HD 15-pin (female) x 1 (RGB/YBPBR/YCBCR x 1)
	SERIAL IN	D-sub 9-pin (female) x 1 (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control
	REMOTE 1 IN	M3 x 1 for wired remote control
	REMOTE 1 OUT	M3 x 1 for link control (for wired remote control)
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
	LAN/DIGITAL LINK	RJ-45 x 1 for network, DIGITAL LINK connection, 100Base-TX, compliant with Art-Net, PLink™(Class 1), Deep Color, HDCP
키스톤 보정	수직: ±40 ° (±28 ° with ET-D75LE6, ±22 ° with ET-D75LE50, ±5 ° with ET-D75LE90) 수평: ±15 °	
렌즈슈프트	수직: ±70 % (±60 % with ET-D75LE6, +78~+96 % with ET-D75LE90) (powered), 수평: ±30 % (±20 % with ET-D75LE6, -13~+27 % with ET-D75LE90) (powered)	
전원	200–240 V AC, 50/60 Hz	
소비전력	2,060W (Standby[Nomal] : 9W / Standby[Eco] : 0.3W)	
소음	46dB (Quad lamp operation)	
크기(W×H×D)	620 x 291 x 800 mm (without lens)	
무게	41 kg (without lens)	