

**World's Smallest and Lightest 30,000lm 3-chip DLP
4K Projector Streamlines Workflow Management**



30,500lm 4K 20,000:1

Item	Description	
DLP™ chip	24.4mm (0.96") (16:10 비율) DLP™ chip ×3	
해상도	WUXGA (1920 x 1200 pixels)	
광 원	Laser diodes (광원수명- Nomal : 20,000 h / Eco : 24,000 h / Quiet : 26,000 h)	
밝 기	Nomal : 30,500lm / 32,000(Center), Eco : 24,000lm / Quiet : 20,000lm	
명암비	20,000:1 (Full On/Full Off , Dynamic Contrast Mode: 3)	
주변조도비	90%	
스크린 사이 즈	1.78-25.4 m (70-1,000 in) with 16:10 aspect ratio 1.78-15.24 m (70-600 in) with the ET-D75LE8, ET-D3LET80 16:10 aspect ratio 5.08-15.24 m (200-600 in) with the ET-D3LEW200, ET-D3LEU100 16:10 aspect ratio 3.05-15.24 m (120-600 in) with the ET-D75LE95, 16:10 aspect ratio	
렌즈	Optional (no lens included with this model)	
터미널	HDMI IN	HDMI x 1, HDCP 2.2 compatible, Deep Color compatible
	DIGITAL LINK	RJ-45 x 1, for network and DIGITAL LINK connections (HDBaseTTM compliant), PLink (class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.2 compatible, Deep Color compatible
	MULTI PROJECTOR SYNC MULTI PROJECTOR SYNC OUT	BNC x 1, TTL high impedance BNC x 1, TTL output: Maximum 10 mA
	SERIAL IN	D-Sub 9 p x 1, RS-232C compliant, for computer control
	SERIAL OUT	D-Sub 9 p x 1, RS-232C compliant, for computer control
	REMOTE 1 IN	M3 stereo mini jack x 1, for remote control (wired)/for projector connection control
	REMOTE 1 OUT	M3 stereo mini jack x 1, for remote control (wired)/for projector connection control
	REMOTE 2 IN	D-Sub 9 p x 1, for contact control
	LAN	RJ-45 x 1, for network connection, PLink (class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
	USB	USB connector (type A) x 1, for connecting the optional Wireless Module (Model No.: AJ-WM50 Series), for connecting USB memory
	DC OUT 1 / DC OUT 2	USB connector (type A) x 2, for power supply only (DC 5 V, 2 A total for two terminals)
	SLOT 1 / SLOT 2	SLOT x 2, SLOT NX specification, for installing the Interface Board
키스톤 보정	수직: ±45° (±40° with ET-D75LE10/ET-D3LEW10/ET-D75LE20/ET-D3LES20, ±28° with ET-D75LE6/ET-D3LEW60, ±22° with ET-D3LEW50, ±15° with ET-D3LEW200, ±8° with ET-D3LEU100, +5° with ET-D75LE95) 수평: ±40° (±15° with ET-D3LEW50/ET-D75LE6/ET-D3LEW60, ±5° with ET-D3LEU100/ET-D3LEW200, 0° with ET-D75LE95)	
렌즈유프트	수직: ±55% (±44% with ET-D75LE6, +68% - +78% with ET-D75LE95, ±55% with ET-D3LEU100, ±48% with ET-D3LEW200) (powered) 수평: ±20% (±15% with ET-D75LE6, ±12% with ET-D75LE95, 0-+25% with ET-D3LEU100, ±15% ET-D3LEW200) (powered)	
소음	Nomal : 49 dB / Quiet : 46 dB	
전원	AC100 V-AC120 V/AC200 V-AC240 V 50 Hz/60 Hz AC100 V-AC120 V, 50 Hz/60 Hz (Brightness is restricted to approximately 1/3)	
소비전력 크기(W×H×D)	2,550W (Nomal : 2,060W / Eco : 1,650W / Quiet : 1,370W / Standby : 14W) 598 x 353 x 780 mm (including protruding parts)	
무게	68.6 kg (151.2 lbs)	