

**Extraordinary SOLID SHINE Power from Compact
and Versatile 1-Chip DLP™ Laser Projectors**



9,400lm WUXGA 10,000:1

Item	Description	
DLP™ chip	17.0 mm (0.67") 대각 (16:10 화면 비율)	
해상도	WUXGA (1920 x 1200 pixels)	
광원	Laser diodes (광원수명 - Nomal/Quiet : 20,000 h / Eco : 24,000 h)	
밝기	10,000 Lumens(Center) / 9,400 Lumens(Normal)	
명암비	10,000:1 (Full On/Full Off, Dynamic Contrast Mode: 3)	
주변조도비	90% (Center-to-corner)	
스크린 사이즈	1.27~15.24 m (50~600 in) with ET-DLE055 1.27~5.08 m (50~200 in) with ET-DLE055 2.54~8.89 m (100~350 in) with ET-DLE035 2.54~10.16 m (100~400 in) with ET-DLE020, 16:10 aspect ratio	
렌즈	Powered zoom (throw ratio 1.71~2.41:1), powered focus F 1.7~1.9, f 25.6~35.7 mm	
단자	SDI IN	BNC x 1: 3G/HD/SD-SDI input
	HDMI IN	HDMI 19-pin x 1 (Compatible with HDCP 2.2, Deep Color, 4K/60p signal input)
	DVI-D IN	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
	RGB 1 IN	RGB x 1 (BNC x 5): RGB/YBPBR/YCBCR/YC/VIDEO
	RGB 2 IN	D-sub HD 15-pin (female) x 1: RGB/YBPBR/YCBCR
	SERIAL/MULTI PROJECTOR SYNC IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
	SERIAL/MULTI PROJECTOR SYNC OUT	DD-sub 9-pin (male) x 1 for link control
	REMOTE 1 IN	M3 x 1 for wired remote control
	REMOTE 1 OUT	M3 x 1 for link control (for wired remote control)
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
	LAN/DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connections (HDBase™ compliant), PLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.2 compatible, Deep Color compatible, 4K/60p signal input)
렌즈쉬프트	수직: -16~+50 % (-16~+40 % with ET-DLE060) (powered) 수평: -10~+30 % (-20~+10 % with ET-DLE020, -10~+19 % with ET-DLE060, -10~+28 % with ET-DLE105/ET-DLE085) (powered)	
키스톤 보정	수직: ±40° (±5° with ET-DLE020, ±16° with ET-DLE060, ±22° with ET-DLE105/DLE85/DLE055, +5° with ET-DLE035) 수평: ±15° (±10 ° with ET-DLE060 (cannot be operated with ET-DLE035/ET-DLE020))	
소음	Nomal : 40dB / Quiet 1 : 36 dB / Quiet 2 : 35 dB	
전원	AC 100~240 V, 50/60 Hz	
소비전력	820W (Nomal : 735W/ Eco : 575W / Long Life 1 : 265W / Long Life 3 : 205W / Quiet 1 : 490 W / Quiet 2 : 365 W)	
크기(W×H×D)	498 x 200 x 581 mm (with supplied lens) 498 x 200 x 538 mm (without lens)	
무게	23.0 kg (with supplied lens), 22.2 kg (without lens)	
캐비닛 재질	성형 플라스틱	
작동 환경	작동 온도 : 0°C- 45°C, 작동 습도 : 10 - 80 % (무결로)	