

**Extraordinary SOLID SHINE Power from Compact
and Versatile 1-Chip DLP™ Laser Projectors**



6,000lm WUXGA 10,000:1

| Item | Description | |
|-----------|--|---|
| DLP™ chip | 17.0 mm (0.67") 대각 (16:10 화면 비율), DLP™ chip x 1 | |
| 해상도 | WUXGA (1920 x 1200 pixels) | |
| 광원 | Laser diodes (광원수명 - Normal : 20,000H / Eco : 24,000H) | |
| 밝기 | 6,000 lm / 6,200 lm (Center) | |
| 명암비 | 10,000:1 (Full On/Full Off, Dynamic Contrast Mode: 3) | |
| 주변조도비 | 90% (Center-to-corner) | |
| 스크린 사이즈 | 1.27~15.24 m (50~600 in) with ET-DLE055 1.27~5.08 m (50~200 in) with ET-DLE055 2.54~8.89 m (100~350 in) with ET-DLE035 2.54~10.16 m (100~400 in) with ET-DLE020, 16:10 aspect ratio | |
| 렌즈 | Powered zoom (throw ratio 1.71~2.41:1), powered focus F 1.7~1.9, f 25.6~35.7 mm | |
| 단자 | SDI IN | BNC x 1: 3G/HD/SD-SDI input |
| | HDMI IN | HDMI 19-pin x 1 (Compatible with HDCP 2.2, Deep Color, 4K/60p signal input) |
| | DVI-D IN | DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only) |
| | RGB 1 IN | RGB x 1 (BNC x 5): RGB/YPBPR/YCBCR/YC/VIDEO |
| | RGB 2 IN | D-sub HD 15-pin (female) x 1: RGB/YPBPR/YCBCR |
| | SERIAL/MULTI PROJECTOR SYNC IN | D-sub 9-pin (female) x 1 for external control (RS-232C compliant) |
| | SERIAL/MULTI PROJECTOR SYNC OUT | DD-sub 9-pin (male) x 1 for link control |
| | REMOTE 1 IN | M3 x 1 for wired remote control |
| | REMOTE 1 OUT | M3 x 1 for link control (for wired remote control) |
| | REMOTE 2 IN | D-sub 9-pin (female) x 1 for external control (parallel) |
| | LAN/DIGITAL LINK | RJ-45 x 1 for network and DIGITAL LINK connections (HDBaseT™ compliant), PJLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.2 compatible, Deep Color compatible, 4K/60p |
| 렌즈시프트 | 수직: -16~+50 % (-16~+40 % with ET-DLE060) (powered) 수평: -10~+30 % (-20~+10 % with ET-DLE020, -10~+19 % with ET-DLE060, -10~+28 % with ET-DLE105/DLE085) (powered) | |
| 키스톤 보정 | 수직: ±40 ° (±22 ° with ET-DLE105/DLE085/DLE055, ±16 ° with ET-DLE060, ±5 ° with ET-DLE020, 0~+5 ° with ET-DLE035) 수평: ±15 ° (±10 ° with ET-DLE060, cannot be operated with ET-DLE035/DLE020) | |
| 소음 | 35 dB (Normal) | |
| 전원 | AC 100~240 V, 50/60 Hz | |
| 소비전력 | 565W (Normal : 490W / Eco : 395W / Long Life 1 : 200W / Long Life 2 : 180W / Long Life 3 : 160W / Standby : 7W) | |
| 크기(W×H×D) | 498 x 200 x 581 mm (with supplied lens) 498 x 200 x 538 mm (without lens) | |
| 무게 | 22.1 kg (with supplied lens), 21.3 kg (without lens) | |
| 캐비닛 재질 | 성형 플라스틱 | |
| 작동 환경 | 작동 온도 : 0°C- 45°C, 작동 습도 : 10 - 80 % (무결로) | |