



Blending High-Brightness SOLID SHINE Laser with Quality LCD Imaging in a Flexible Solution



5,500lm	WXGA	3,000,000:1
----------------	-------------	--------------------

Item	Description	
패널	19.3 mm (0.76") (16:10 비율) LCD × 3	
해상도	WXGA (1,280 x 800 pixels)	
광 원	Laser diodes (광원수명 : 20,000H)	
밝 기	5,500 Lumens	
명암비	3,000,000:1 (Full on/off, Dynamic Contrast Mode: ON)	
주변조도비	90%	
스크린 사이 즈	1.02-10.16 m (40-400 in) 16:10 aspect ratio 1.52-10.16 m (60-400 in) with the ET-ELW22, 16:10 aspect ratio	
렌즈	1.6x Powered zoom (Throw Ratio 1.6-2.8 :1), focus (F = 1.7-2.3, f = 26.8-45.5 mm)	
터미널	HDMI 1 IN	HDMI 19 pin, HDCP and Deep color compatible
	HDMI 2 IN	HDMI 19 pin, HDCP and Deep color compatible
	RGB 1 IN	BNC (female) x 5
	RGB 2 IN	D-Sub 15 p (female) x 1
	MONITOR OUT	D-Sub 15 p (female) x 1
	VIDEO IN	Pin jack x 1
	AUDIO IN 1	M3 stereo jack x 1(L-R)
	AUDIO IN 2	M3 stereo jack x 1(L-R)
	AUDIO IN 3	Pin jack x 2(L-R)
	VARIABLE AUDIO OUT	M3 jack, 0 V[rms] to 2.0 V[rms] variable
	SERIAL IN	D-sub 9 pin, RS-232C compliant
	REMOTE 1	D-Sub 9 p (female) x 1,
	REMOTE 2	M3 jack x 1(L-R) for link control
	LAN	RJ-45 x 1 for network connection, 10/100Base-TX, compliant with PLink™(Class 2)
	DIGITAL LINK / LAN	RJ-45 x 1 for network and DIGITAL LINK (video/network/serial control) connection, 100Base-TX, compliant with PLink™(Class 2), Deep Color, HDCP
	VIEWER / PAIRING	USB type-A x 1
DC OUT	USB type-A x 1(DC 5V, 2A(Max))	
키스톤 보정	수직: ±35° 수평: ±35°	
렌즈쉬프트	수직: ±67 % (powered) 수평: ±35 % (powered)	
소음	Nomal/Eco : 32 dB / Quiet : 26 dB	
스피커	10 W (모노)	
전원	100-240 V AC, 50/60 Hz	
소비전력	415W (Standby [Nomal] : 22 W / [Eco] : 0.5 W)	
크기(W×H×D)	560 x 205 x 443 mm (with supplied lens)	
무게	Approximately 16.9kg (with supplied lens)	