

Ultra-Bright 4K+ SOLID SHINE Laser Projector Delivers Flagship Image Quality for Rental and Staging



26,000lm **4K+** **20,000:1**

Item	Description	
DLP™chip	22.9 mm (0.9") (16:10 비율) DLP™chip ×3	
해상도	4K+ (2560 x 1600 pixels) when Quad Pixel Drive set to OFF	
광 원	Laser diodes (광원수명 - Nomal : 20,000 h / Long Life 3 : 87,600 h)	
밝 기	Nomal : 21,600lm/22,500lm(Center) / High : 26,000lm/27,000lm(Center)	
명암비	20,000:1 (Full On/Full Off , Dynamic Contrast Mode: 3)	
주변조도비	90%	
스크린 사이즈	1.78-25.4 m (70-1,000 in) with 16:10 aspect ratio 1.78-15.24 m (70-600 in) with the ET-D75LE8, 16:10 aspect ratio 3.05-15.24 m (120-600 in) with the ET-D75LE95, 16:10 aspect ratio	
렌즈	Optional (no lens included with this model)	
터미널	SDI IN 1	BNC x 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-A), Dual-link 3G-SDI (Link 1), Quad-link HD/3G-SDI (Link 1)
	SDI IN 2	BNC x 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-B), Dual-link 3G-SDI (Link 2), Quad-link HD/3G-SDI (Link 2)
	SDI IN 3	BNC x 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-A), Dual-link 3G-SDI (Link 1), Quad-link HD/3G-SDI (Link 3)
	SDI IN 4	BNC x 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-B), Dual-link 3G-SDI (Link 2), Quad-link HD/3G-SDI (Link 4)
	MULTI PROJECTOR SYNC IN	BNC x 1
	MULTI PROJECTOR SYNC OUT	BNC x 1
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control
	REMOTE 1 IN	M3 x 1 for wired remote control
	REMOTE 1 OUT	M3 x 1 for wired remote control, link control
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
	DIGITAL LINK/LAN	RJ-45 x 1 for network, DIGITAL LINK connection(HDBase™ compliant), 100Base-TX, compatible with Art-Net,PJLink™ (class 1), Deep Color, HDCP 2.2
	DC 1/2 OUT	USB connector (Type A), power supply only (DC 5V, max. 900 mA)
Expansion Slot	SLOT1/SLOT2 (total of two terminals, vacant) for interface boards, SLOT NX compatible	
키스톤 보정	수직: ±40° (±28° with the ET-D75LE6 , ±22° with the ET-D75LE50 , 0~+5° with the ET-D75LE90) 수평: ±15° (cannot be operated when used with the ET-D75LE90)	
렌즈슈프트	수직: ±59 % (±56 % with ET-D75LE6, +68 ~+84 % with ET-D75LE95) (powered) 수평: ±29 % (±19 % with ET-D75LE6, ±21 % with ET-D75LE95) (powered)	
소음	49 dB	
전원	AC 100-120 V (12 A) / AC 200-240 V (16 A), 50/60 Hz (brightness restricted with voltage lower than 200 V)	
소비전력	2,950W (Nomal : 2,000W / High : 2,400W / Long Life 1 : 1,190-1,780W / Long Life 3 : 926-1,580W)	
크기(W×H×D)	700 × 418 × 1,250 mm (including protruding parts)	
무게	83 kg (183 lbs.)	