

## Taking Laser Projection to a Whole New Level.



**12,000lm**   **WUXGA**   **20,000:1**

Item	Description	
DLP™ chip	24.4 mm (0.96") (16:10 비율) DLP™ chip × 3	
해상도	6,912,000 (1,920 × 1,200 × 3) pixels	
광 원	Laser diodes (광원수명 - Normal: 20,000H / Eco: 24,000H)	
밝 기	12,000 Lumens	
명암비	20,000:1 (Full On/Off)	
주변조도비	90%	
스크린 사이즈	1.78–25.4 m (70–1000 in) with 16:10 aspect ratio 1.78–15.24 m (70–600 in) with the ET-D75LE8, 16:10 aspect ratio 3.05–15.24 m (120–600 in) with the ET-D75LE90, 16:10 aspect ratio	
렌즈	Optional powered zoom/focus lenses and fixed-focus lens	
터미널	SDI IN 1	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (LINK-A), Dual-link 3G-SDI (LINK 1)
	SDI IN 2	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (LINK-B), Dual-link 3G-SDI (LINK 2)
	HDMI IN	HDMI 19-pin × 1 (Deep Color, compatible with HDCP)
	DVI-D IN	DVI-D 24-pin × 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
	RGB 1 IN	RGB × 1 (BNC × 5): RGB/YBPBR/YCBCR/YC/VIDEO
	RGB 2 IN	D-sub HD 15-pin (female) × 1: RGB/YBPBR/YCBCR
	3D SYNC 1 IN/OUT	BNC × 1: 3D timing signal
	3D SYNC 2 OUT	BNC × 1: 3D timing signal
	SERIAL IN	D-sub 9-pin (female) × 1 for external control (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) × 1 for link control
	REMOTE 1 IN	M3 × 1 for wired remote control, link control
	REMOTE 1 OUT	M3 × 1 for wired remote control, link control
	REMOTE 2 IN	D-sub 9-pin (female) × 1 for external control (parallel)
	DIGITAL LINK/LAN	RJ-45 × 1 for network, DIGITAL LINK connection, 100Base-TX, compatible with Art-Net, PLink™ (class 1), Deep Color, HDCP
키스톤 보정	수직: ±40° (±28° with the ET-D75LE6, ±22° with the ET-D75LE50, 0~+5° with the ET-D75LE90) 수평: ±15° (cannot be operated when used with the ET-D75LE90)	
렌즈쉬프트	수직: ±55 % (±44 % with the ET-D75LE6, +73~+78 % with the ET-D75LE90) (powered) 수평: ±20 % (±15 % with the ET-D75LE6, ±6 % with the ET-D75LE90) (powered)	
소음	43dB	
전원	AC 100–240 V, 50/60 Hz	
소비전력	1,200 W (Nomal : 800 W / Eco : 680 W / Long Life 1 : 620 W / Long Life 2 : 590 W / Long Life 3 : 550 W)	
크기(W×H×D)	578 × 270 × 725 mm(렌즈 미포함), 578 × 323.5 × 740 mm (렌즈포함)	
무게	44 kg (렌즈 무장착)	