

Evolved 1-chip DLP Projectors

with Powerful Contrast Transform Your Experience

with a Smooth, Frictionless Workflow



10,000lm	WUXGA	25,000:1
-----------------	--------------	-----------------

Item	Description	
패널	0.8" (16:10 비율) 1chip DLP	
해상도	WUXGA (1,920 x 1,200 pixels)(with Quad Pixel Drive)	
광 원	Laser diode (광원수명 - Nomal : 20,000h / Eco : 24,000h)	
밝 기	10,000 Lumens	
명암비	25,000:1	
주변조도비	90%	
스크린 사이즈	70-700 in, 16:10 aspect ratio	
렌즈	Power zoom (throw ratio 1.36~2.10 :1), Power Focus(F 1.84-2.31) (optional lenses also available)	
단자	HDMI 1IN/ 2IN	HDMI x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input4)
	DisplayPort	DisplayPort x 1 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input4)
	MULTI SYNC IN	BNC x 1 (TTL high impedance)
	MULTI SYNC OUT	BNC x 1 (TTL output: Maximum 10 mA)
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
	REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control
	REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control (for wired remote control)
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
	LAN	RJ-45 x 1 for network connection, PLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
	USB	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory stick
	DC OUT	USB connector (Type A) x 1 (for power supply, DC 5 V, 2 A)
	SLOT	Open slot for function boards, Intel® SDM compatible
렌즈쉬프트	수직: ±60 % (powered) , 수평: ±29 % (powered)	
키스톤	수직: ±40° (powered) , 수평: ±40° (powered)	
소음	Nomal/Eco : 36 dB / Quiet : 33 dB	
전원	100-240 V AC, 50/60 Hz	
소비전력	Nomal : 675W / Max : 810W / Eco : 525W / Standby : 12W	
크기(W×H×D)	498 x 212 x 648 mm (including standard zoom lens)	
무게	Approximately 28.7kg (including standard zoom lens)	