



**Immersive for All:**

**Light & Compact 1-Chip DLP**

**4K Projectors Maximize your Efficiency**

<b>7,500lm</b>	<b>4K</b>	<b>15,000:1</b>
----------------	-----------	-----------------

Item	Description	
패널	0.65" (16:9 비율) 1chip DLP	
해상도	4K (3,840 x 2,160 pixels)(with Quad Pixel Drive)	
광 원	Laser diode (광원수명 - Nomal : 20,000h / Eco : 24,000h)	
밝 기	7,500 Lumens	
명암비	15,000:1	
주변조도비	90%	
스크린 사이즈	50-600 in (with ET-DLE060, DLE085, DLE105, DLE150, DLE170, DLE250, DLE350, DLE450) 50-200 in (with ET-DLE055) 100-350 in (with ET-DLE035) 100-400 in (with ET-DLE020)	
렌즈	Optional powered zoom/focus lenses	
단자	HDMI 1IN/ 2IN	HDMI x 2 (Deep Color, compatible with HDCP2.3, 4K/60p signal)
	SERIAL IN	D-sub 9-pin (female) x 1 (for external control (RS-232C compliant))
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
	REMOTE IN	M3 stereo mini-jack x 1 for wired remote control
	REMOTE OUT	M3 stereo mini-jack x 1 for link control (for wired remote control)
	DIGITAL LINK/LAN	RJ-45 x 1 (for network and DIGITAL LINK connections (HDBase™ compliant), PJLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.3 compatible, Deep Color compatible, 4K/60p signal input)
	LAN	RJ-45 x 1 (for network connection, PJLink™ (class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible)
	USB (DC OUT)	USB connector (type A) x 1 (for connecting the optional Wireless Module (Model No.:AJ-WM50 Series), for connecting USB memory, for power supply)
SLOT	SLOT x 1 (Open slot for function boards, Intel® SDM compatible)	
렌즈쉬프트	수직: -18~+66%, 수평: -10~+30 %	
키스톤	수직: ±40°, 수평: ±40°	
소음	Nomal/Eco : 35 dB / Quiet : 32 dB	
전원	100-240 V AC, 50/60 Hz	
소비전력	Nomal : 520W / Max : 650W / Eco : 400W / Standby : 14W	
크기(W×H×D)	498 x 170 x 440 mm (excluding protrusions)	
무게	Approximately 16.6kg (excluding the optional lens)	