

## The World's Smallest, Lightest and Quietest Projector



**14,000lm** **WUXGA** **3,000,000:1**

Item	Description	
패널	25.4 mm (1.0") (16:10 비율) LCD × 3	
해상도	WUXGA (1,920 x 1,200 pixels)	
광 원	Laser diodes (광원수명 : 20,000H)	
밝 기	14,000 Lumens	
명암비	3,000,000:1 (Full On/Full Off)	
주변조도비	85%	
스크린사이즈	2.03~15.24 m (80~500 in), 16:10 aspect ratio	
	2.54~10.16 m (100~400 in), 16:10 aspect ratio(with ET-EMU100)	
	2.03~12.7 m (80~500 in), 16:10 aspect ratio(with ET-EMT800)	
렌즈	Optional powered zoom lenses	
터미널	HDMI IN	HDMI 19-pin x 1 (Compatible with HDCP 2.3, DeepColor, 4K/60p signal input,CEC supported)
	SDI IN	BNC x 1 (3G/HD/SD-SDI input)
	SERIAL/MULTI PROJECTOR SYNC IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
	SERIAL/MULTI PROJECTOR SYNC OUT	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
	REMOTE 1 IN	D-sub 9-pin (female) × 1 for external control (parallel)
	REMOTE 2 IN	M3 x 1 for wired remote control
	REMOTE 2 OUT	M3 x 1 for link control (for wired remote control)
	DIGITAL LINK	RJ-45 x 1 for network and DIGITALLINK connections(HDBaseTTM compliant), PJLink(class2)compatible,100Base-TX,Art-Net compatible, HDCP 2.3 compatible, DeepColor compatible, 4K/60p signal input
	LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PJLink™ [Class 2], Art-Net)
	DC OUT	USB Connector (Type A) x 1 (for power supply (DC 5V, maximum 2A))
USB	USB Connector (Type A) x 1 (Output 5 V/2 A)	
키스톤 보정	수직: ±45° (±5° with ET-EMU100, ±14° with ET-EMW200/EMW300, ±22° with ET-EMW400/EMW500) 수평: ±40° (±8° with ET-EMW200/EMW300, ±15° with ET-EMW400/EMW500)	
렌즈쉬프트	수직: ±60 % (-20~+50 % with ET-EMU100, ±40 % with ET-EMW200, ±50 % with ET-EMW300) (powered) 수평: ±20 % (±19 % with ET-EMW200) (powered)	
소음	Nomal : 35 dB / Quiet : 30 dB	
전원	100-240 V AC, 50/60 Hz	
소비전력	800W (Nomal : 690 W / Quiet : 445 W / Shutter : 10 W)	
크기(W×H×D)	650 x 211 x 440 mm (Without lens)	
무게	Approximately 22.5kg	