

Expand Production Possibilities And Revolutionize Your Workflow with Next-Generation 4K Projectors



15,000lm	WUXGA	25,000:1
-----------------	--------------	-----------------

Item	Description	
패널	0.8" (16:10 비율) 1chip DLP	
해상도	WUXGA (1920 x 1200 dots)	
광 원	Laser diodes (광원수명 : 20,000H)	
밝 기	15,000 Lumens	
명암비	25,000:1	
주변조도비	90%	
스크린사이즈	70-700 in	
렌즈	전동 줌 (throw ratio 1.36~2.10 :1), 전동 포커스 F = 1.84-2.31 (Optional powered zoom/focus lenses)	
터미널	HDMI 1/2 IN	HDMI™ x 2 Deep Color, compatible with HDCP2.3, 4K/60p signal
	DisplayPort IN	DisplayPort x 1 Deep Color, compatible with HDCP 2.3, 4K/60p signa
	MULTI SYNC IN	BNC x 1 TTL high impedance
	MULTI SYNC OUT	BNC x 1 TTL output: Maximum 10 mA
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
	REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control
	REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control (for wired remote control)
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)
	LAN	RJ-45 x 1 for network connection, PLink™ (class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
	USB	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory stick
	DC OUT	USB connector (Type A) x 1 for power supply, DC 5 V, total of 2 A
SLOT	SLOT x 1 Open slot, for function boards, Intel® SDM compatible	
키스톤 보정	수직: ±40°, 수평: ±40° (with ET-C1S600)	
렌즈쉬프트	수직: ±60 % (powered), 수평: ±50 % (powered)	
소음	Normal/Eco : 42 dB, Quiet : 38 dB	
전원	100-240 V AC, 50/60 Hz	
소비전력	[MAX] 1090 W (11.5-4.7 A) (1100VA), 1040 W (200-240 V) [NORMAL]: 945 W (100-120 V), 900 W (200-240 V) [ECO]: 730 W (100-120 V), 700 W (200-240 V) [QUIET]: 725 W (100-120 V), 695 W (200-240 V)	
크기(W×H×D)	498 x 212 x 648 mm (with standard zoom lens)	
무게	Approximately 28.7kg (with standard zoom lens)	