

*Smooth and Detailed 4K Images from the Smallest,
Lightest LCD Projector in Its Class*



6,500lm 4K 5,000,000:1

Item	Description	
패널	16.3mm (0.64") (16:10 비율) LCD × 3	
해상도	4K (3,840 × 2,400)	
광 원	Laser diodes (광원수명 - Nomal : 20,000h / Eco : 24,000h)	
밝 기	6,500 Lumens	
명암비	5,000,000:1	
주변조도비	85%	
투사비	Throw Ratio 1.09–2.21:1 (Corresponding value. When used together with optical zoom.)	
스크린 사이즈	0.76–7.62 m [30–300 in], 16:10 aspect ratio	
렌즈	1.6x Manual zoom(throw ratio: 1.09–1.77:1), F = 1.58–1.91, f = 15.3–24.6 mm	
단자	HDMI 1 IN / 2 IN	HDMI 19-pin x 2 (Compatible with HDCP, Deep Color, 4K/30p signal input), CEC supported
	HDMI 1 IN / 2 IN	HDMI™ 19-pin x 1 (Compatible with HDCP, Deep Color, 4K/60p signal output)
	AUDIO IN	M3 stereo mini-jack x 1
	AUDIO OUT	M3 stereo mini-jack x 1
	SERIAL IN	D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)
	DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITALINK connection(video/network/serial control)(HDBaseT compliant), 100Base-TX (Compatible with PLink [Class 2], HDCP, Deep Color, 4K/30p7 signal input)
	LAN	RJ-45 x 1 for network control, 10Base-T, 100Base-TX, compatible with PLink™ [Class 2]
	USB(VIEWER /WIRELESS/DC OUT)□	USB connector (Type A) x 1 for Memory Viewer function, optional AJ-WM50 Series Wireless Module, power supply (DC 5 V, maximum 2 A9)
키스톤 보정	수직 : ±25° / 수평 : ±35°	
렌즈쉬프트	수직: 0~+44 %, 수평: ±20 %	
소음	Nomal/Eco : 35 dB / Quiet : 25 dB	
전원	100–240 V AC, 50/60 Hz	
소비전력	[MAX] 320W / [NORMAL] 280W / [ECO]: 215W [QUIET1]: 245W / [QUIET2]: 210W	
크기(W×H×D)	399 x 133 x 348 mm (with feet at shortest position)	
무게	Approximately 7.1kg	